振石集团东方特钢有限公司
ZHENSHI GROUP EASTERN SPECIAL STEEL CO., LTD.

产品质量证明书
INSPECTION CERTIFICATE

地址:浙江省嘉兴市南湖区新丰镇工业功能区（北区）
ADD: (NORTH) INDUSTRIAL FUNCTION ZONE, XINFENG TOWN, NANHU DISTRICT, JIAXING CITY, ZHEJIANG PROVINCE, CHINA
电话TEL: +86-573-88620697　　邮编(P.C): 314500

订货单位 CUSTOMER		产品名称 PRODUCT	热轧不锈钢带 HOT-ROLLED STAINLESS STEEL STRIPS	证书号 CERTIFICATE NO.	
收货单位 PURCHASER		合同号 CONTRACT NO.		交货日期 DATE OF DELIVERY	2025年12月18日
牌　号 GRADE	310S	订单号 ORDER NO	/	签发日期 DATE OF ISSUE	2025年12月19日
标准 SPECIFICATION	ASTM A240M-2023	交货状态 DELIVERY STATUS	NO.1固溶、酸洗	ISO9001证书号 ISO9001 CERTIFICATE NUMBER	CN10/21015

序号	钢卷 COIL NO.	炉号 HEAT NO.	规格及重量 MATERIAL DESCRIPTION 厚度 THICKNESS mm	宽度 WIDTH mm	长度 LENGTH mm	件数 NUMBER 件	重量 WEIGHT kg	C	Si	Mn	P	S	Cr	Ti	Ni	Mo	N	Cu	Ce	Al	Nb	Co	W	PREN
1			15.75	1525	C	1	24200	0.039	0.65	1.07	0.016	0.001	25.62	/	19.10	/	/	/	/	/	/	/	/	/
2			11.75	1525	C	1	20185	0.036	0.67	1.05	0.018	0.001	25.58	/	19.10	/	/	/	/	/	/	/	/	/
3																								
4																								
5																								
合计(TOTAL)						2	44385																	

序号	钢卷 COIL NO.	拉伸试验TENSILE TEST 规定塑性延伸强度 (P.S.) Rp1.0 Mpa	Rp0.2 Mpa	抗拉强度 (T.S.) Rm Mpa	断后伸长率 (EL.) A50 %	硬度 HARDNESS HRBW 1	2	冲击试验 IMPACT TEST 方向 DIR.	宽度 W. mm	温度 TEM. ℃	ABSORBED ENERGY (J) 吸收功 (J) KV 1	2	3	AVE.	晶间腐蚀 INTERGRANULAR CORROSION TEST	晶粒度 GRAIN SIZE	超声探伤 UT	侧向膨胀量 LATERAL EXPANSION VALUES	点蚀 [g/(m2*d)]
1		/	277	590	64	89	88	/	/	/	/	/	/	/	/	/	/	/	/
2		/	284	585	60	87	88	/	/	/	/	/	/	/	/	/	/	/	/
3																			
4																			
5																			

公司印章
Company Seal

质量负责人
QUALITY MANAGER

备注 REMARKS

1. 本产品已通过ISO9001质量认证许可(THE PRODUCTS HAVE PASSED THE ISO9001 QUALITY CERTIFICATION LICENSE.)
2. 谨保证以上所有的内容真实准确(WE HEREBY CERTIFY THE ABOVE STATEMENT TO BE TRUE AND CORRECT IN EVERY DETAIL.)
3. 热处理:固溶+水冷处理（SOLUTION AND QUENCHING IN WATER）
4. 材料无放射性污染（The material is free from Radioactive Contamination.）
5. 产品的尺寸公差、外观检查符合ASTM A480M相关要求（Dimension control,visual inspection acc.to ASTM A480M ）

注释 NOTES

TR.: (Transverse)横向, L.: (Longitudinal)纵向, DIR.:(Direction)方向, W.:(Width)宽度, TEM.:(Temperature)温度, EL.:(Elongation)断后伸长率, Y.S.:(Yield Strength)屈服强度, T.S.:(Tensile Strength)抗拉强度, AVE.:平均值

REFERENCE SAMPLE | Commercial identifiers redacted | Not valid for shipment acceptance
Technical values remain as shown in the supplied document. This is a flattened, privacy-redacted reference copy.