TISCO 太钢不锈

生产单位：山西太钢不锈钢股份有限公司
Production: SHANXI TAIGANG STAINLESS STEEL CO.,LTD.

产品质量证明书
INSPECTION CERTIFICATE

订货单位： Customer：	产品名称： 不锈钢热轧钢带 Product： Hot rolled stainless steel coil	标准Specification GB/T713.7-2023,EN10028-7:2016	牌号Grade S31603/1.4404/316L
收货单位： Purchaser：	供货状态： 1D/No.1 固溶 酸洗 不切边 Condition： 1D/No.1;Solution annealed;Pickling;M	ASME SA-240/SA-240M-2025	

合同号Mill'S No.	客户订单Customer Order No.	交货单号Delivery Order No.	证书编号Certificate No.				车号Train Wagon No.	

序号 No	材料号 Material No.	炉号 Heat No.	试验批 Test No.	规格 Dimensions(mm)	数量 Quantit	重量 Weight (t)	分析 Max. Min.	C%	Si%	Mn%	P%	S%	Cr%	Ni%	Mo%	N%
1		A2602561		8*2000	1	27.920	H	0.021	0.48	1.07	0.029	0.001	16.50	10.11	2.04	0.03
				合计Total	1	27.920		尺寸及外观Acceptable Visual d Dimensions:合格OK								

序号 No.	位置 方向 P.D.	屈服强度 Y.S. Rp0.2 MPa 常温	屈服强度 Y.S. Rp1.0 MPa 常温	抗拉强度 T.S. Rm MPa 常温	伸长率 EL. A5 % 常温	伸长率 EL. A50 % 常温	硬度 Hardness HBW 常温	硬度 Hardness HBW 常温	晶间腐蚀 I G C
	Max. Min.								
1	J2 J1	260	290	600	58	61	165	165	OK

注释 Notes：M=Not cutting edge；H=熔炼分析Heat analysis；P=成品分析Product analysis；D=电渣重溶分析Electroslag remelting； Y.S.=Yield Strength； 常温 = Normal Temperature (Room Temperature)； T.S.=Tensile Strength； EL.=Elongation； A5:Lo=5.65SQRT(So)； A50:Lo=50mm； I G C=Intergranular corrosion;J=头尾Top/Bottom；2=横向Transverse；1=纵向Longitudinal；

腐蚀方法Corrosion Methods
GB/T 4334 E

声明 Declare：本产品仅限国内销售不得出口，经销商向用户出具本质量证明书复印件需加盖其公章。
This product is for domestic sales in China only. Export is not allowed. This certificate, if provided by a re-seller in photocopy, is invalid unless with the re-seller's company stamp.

备注 Remarks：

山西太钢不锈钢股份有限公司 质量证明书专用章

声明：本产品已按上述要求制造和检验，结果符合要求,特此证明。
We Hereby Certify That Material Described Herein Has Manufactured And Tested With Satisfactory Results In Accordance With The Requirements Of The Above Material Specification.

中国 山西 太原市尖草坪街2号，邮编030003
No.2 Jiancaoping Street, Taiyuan City, Shanxi Province，030003,P.R. China
服务热线 After-sale Service:[illegible]，400-653-1998

质量负责人Quality Manager

证书类型Certificate Type： EN 10204 3.1

Certified in accordance with PED 2014/68/EU,Annex I.,Paragraph 4.3 by TüV Rheinland Industrie Service GmbH (0035)
Certified in accordance to PER 2016 Schedule 2, Paragraph 31.8 by LRQA Verification Limited (UK AB No. 0038)

日期Date. 07/02/2026 页码Page 1/1

SHEYE METAL | www.sheyemetal.com | Privacy-redacted public reference copy
Parent coil: 316L, 8 x 2000 mm; heat A2602561. Finished plate length is not certified by this coil document.
Customer/purchaser fields were blank in the supplied copy. Other commercial identifiers and personal signatures removed.
Original technical data and validity restrictions remain visible. This derivative is not an original delivery certificate.